



Inner beam	Beam	AI-23-62250-1200-820-8	Suspension	SPW SLU 12016 ECM	Driving bogie	A0097500 (H=1830)
Connections	Front adaptor	A0097330	Axles	SPW MAGL 12016 ECO	Side view	[7] UND 180 element, [9] UNF 240 element
300	Chassis	A0097330	Motor/Power	+ 205 / -79 (incl. bump)	Stake pockets	Ø6-Ø8 x 30 mm
1000	Inner beam	A0097345	Type	2x3/20 R17.5	Clear	Height 330mm max, clear 37mm min.
1500	Center beam	---	FCM wheel load	Min. 30,000 kg	Headings	E-1330
2000	Outer beam	A0097345	Single load	Min. 30,000 kg	Drive shafts	ø13
2500	Rear adaptor	A0097350	Clutch	---	Chassis number	3600-08
3000	Slings others notes	A0097340	Client	Shinko Steel Co. Ltd.	Chassis number	294320R1101040
3500	Steering	A0097335 + H-18303				
4000	Rear	A0097360 + A0097345				
4500	Leveling	ES04118				
5000	Spine wheel carrier	see location				
	Outfitters	---				

BRUNNEN BRUNNEN B.V. SPINNIK, HANNOVER Industriestraße 18 30634 NO SPRUNGEN TELEFON +49 5103 1377860 TELEFAX +49 5103 1377868 E-MAIL info@brunnenv.de		Copyright © BRUNNEN B.V. 2008 1101040	Specification modifications Drawn PH Checked HZ Date 20-04-11 Overall 1101040 Formed AT Intolerance ISO 2768-M	Projection
---	--	---	--	----------------

TRI AXLE EXTENSIBLE LOW LOADER

1101040